X International.

Material Safety Data Sheet INTERCURE 99 BASE ULTRA DEEP PART A

Bulk Sales Reference No.: MSDS Revision Date: MSDS Revision Number: Sales Order: {SalesOrd} QNA044 09/30/2014 A6-

1. Identification of the preparation and company **1.1. Product identifier INTERCURE 99 BASE ULTRA DEEP PART A Product Identity Bulk Sales Reference No. QNA044** 1.2. Relevant identified uses of the substance or mixture and uses advised against **Intended Use** See Technical Data Sheet. **Application Method** See Technical Data Sheet. 1.3. Details of the supplier of the safety data sheet **Company Name** International Paint LLC 6001 Antoine Drive Houston Texas 77091 Emergency **CHEMTREC (USA)** (800) 424-9300 **International Paint** (713) 682-1711 **Poison Control Center** (800) 854-6813 **Customer Service International Paint** (800) 589-1267 Fax No. (800) 631-7481

2. Hazard identification of the product

2.1. Classification of the substance or mixture

Flam. Liq. 3;H226	Flammable liquid and vapor.
Skin Sens. 1;H317	May cause an allergic skin reaction.
Aquatic Chronic 3;H412	Harmful to aquatic life with long lasting effects.

2.2. Label elements

Using the Toxicity Data listed in section 11 & 12 the product is labelled as follows.



H226 Flammable liquid and vapor.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P260 Do not breathe mist / vapors / spray.

P261 Avoid breathing dust / fume / gas / mist / vapors / spray.

P262 Do not get in eyes, on skin, or on clothing.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection.

P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P302+352 IF ON SKIN: Wash with soap and water.

P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P331 Do NOT induce vomiting.

P333+313 If skin irritation or a rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P370 In case of fire: Use water spray, fog, or regular foam.

P403+233 Store in a well ventilated place. Keep container tightly closed.

P501 Dispose of contents / container in accordance with local / national regulations.

HMIS Rating	Health: 2	Flammability: 3	Reactivity: 0
-------------	-----------	-----------------	---------------

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
SECONDARY DIAMINES CAS Number: TS-KH8070	25 - 50		[1]
Barium sulfate CAS Number: 0007727-43-7	10 - 25		[1][2]
Methyl n-amyl ketone CAS Number: 0000110-43-0	1.0 - 10	Flam. Liq. 3;H226 Acute Tox. 4;H332 Acute Tox. 4;H302	[1][2]
Talc CAS Number: 0014807-96-6	1.0 - 10		[1][2]
Ethyl 3-ethoxypropionate CAS Number: 0000763-69-9	1.0 - 10	Flam. Liq. 2;H225 Eye Irrit. 2;H319	[1]
Silica, amorphous CAS Number: 0007631-86-9	1.0 - 10		[1][2]
Aluminum oxide CAS Number: 0001344-28-1	1.0 - 10		[1]
Potassium oxide CAS Number: 0012136-45-7	1.0 - 10		[1]
Bis (1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	0.10 - 1.0	Skin Sens. 1;H317	[1]

CAS Number: 0041556-26-7	Aquatic Chronic 1;H410 Aquatic Acute 1;H400	
DECANEDIOIC ACID, METHYL 1,2,2,6,6-PENTAMETHYL- 4-P CAS Number: 0082919-37-7	Skin Sens. 1;H317 Aquatic Chronic 1;H410	[1]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

4. First aid measures

4.1. Description of first a	
General	Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Eyes	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin	In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.
Ingestion	If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person.
4.2. Most important sym	ptoms and effects, both acute and delayed
Overview	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing.
Inhalation	Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea.
Eyes	Risk of serious damage to eyes. Do not get in eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific condition of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thouroughly cleaned, or discarded after each use.
Skin	Causes skin irritation. May cause delayed skin irritation. May cause allergic skin reaction. May be harmful if absorbed through the skin.
Ingestion	Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness.
Chronic effects	Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.

5. Fire-fighting measures

5.1. Extinguishing media

CAUTION: This product has a very low flashpoint. Use of water spray when fighting fire may be inefficient. SMALL FIRES: Use dry chemical, CO2, water spray or alcohol-resistant foam. LARGE FIRES: Use water spray, fog, or alcohol-resistant foam. Do not use straight streams. Move containers from fire area if you can do so without risk. Runoff from fire control may cause pollution. Dike fire control water for later disposal. Do not scatter the material.

5.2. Special hazards arising from the substance or mixture

FLAMMABLE/COMBUSTIBLE MATERIALS: Will be easily ignited by heat, sparks or flames. Vapors may form

explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks) creating a vapor explosion hazard. Runoff to sewers may create fire or explosion hazard. Containers may explode when heated.

5.3. Advice for fire-fighters

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water courses.

ERG Guide No. 127

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only nonsparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material.

6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

6.3. Methods and material for containment and cleaning up

CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 25 to 50 meters (80 to 160 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet).

7. Handling and storage

7.1. Precautions for safe handling

Handling

Vapors may cause flash fire or ignite explosively.

In Storage

Keep away from heat, sparks and flame.

7.2. Conditions for safe storage, including any incompatibilities

Store between 40-100F (4-38C).

Do not get in eyes, on skin or clothing.

Strong oxidizing agents.

Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone.

7.3. Specific end use(s)

Close container after each use.

Wash thoroughly after handling.

Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

8. Exposure controls and personal protection

8.1. Control parameters

Ingredient Methyl n-amyl ketone	Source	Value
Methyl n-amyl ketone		
	OSHA	100 ppm TWA; 465 mg/m3 TWA
	ACGIH	50 ppm TWA
	NIOSH	100 ppm TWA; 465 mg/m3 TWA800 ppm IDLH
	Supplier	No Established Limit
	OHSA, CAN	25 ppm TWA; 115 mg/m3 TWA
	Mexico	50 ppm TWA LMPE-PPT; 235 mg/m3 TWA LMPE-PPT100 ppm STEL [LMPE-CT]; 465 mg/m3 STEL [LMPE-CT]
	Brazil	No Established Limit
Ethyl 3-ethoxypropionate	OSHA	No Established Limit
	ACGIH	No Established Limit
	NIOSH	No Established Limit
	Supplier	No Established Limit
	OHSA, CAN	50 ppm TWA; 300 mg/m3 TWA
	Mexico	No Established Limit
	Brazil	No Established Limit
Aluminum oxide	OSHA	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)
	ACGIH	No Established Limit
	NIOSH	No Established Limit
	Supplier	No Established Limit
	OHSA, CAN	No Established Limit
	Mexico	10 mg/m3 TWA LMPE-PPT
		No Established Limit
Silica, amorphous		No Established Limit
		No Established Limit
		6 mg/m3 TWA3000 mg/m3 IDLH
		No Established Limit
Barium sulfate		15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)
Danum sullate		10 mg/m3 TWA (total dust), 5 mg/m3 TWA (tespirable fraction)
		10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)
		No Established Limit
		No Established Limit
Potopoium ovide		No Established Limit
Polassium oxide		No Established Limit
		No Established Limit
		No Established Limit No Established Limit
		No Established Limit
		No Established Limit
		No Established Limit
laic	ACGIH	No Established Limit 2 mg/m3 TWA (particulate matter containing no asbestos and <1%
	NIOSH	crystalline silica, respirable f 2 mg/m3 TWA (containing no Asbestos and <1% Quartz, respirable dust1000 mg/m3 IDLH (containing no achestos and <1% guartz)
	Cuppling	dust)1000 mg/m3 IDLH (containing no asbestos and <1% quartz)
	OHSA, CAN	No Established Limit 2 mg/m3 TWA (containing no Asbestos and <1% Crystalline silica, respirable)
	Mexico	2 mg/m3 TWA LMPE-PPT (respirable fraction)
		Supplier OHSA, CAN Mexico Brazil Ethyl 3-ethoxypropionate OSHA ACGIH NIOSH Supplier OHSA, CAN Mexico Brazil OHSA, CAN Mexico Brazil OSHA Aluminum oxide OSHA ACGIH NIOSH Supplier OHSA, CAN Mexico Brazil Silica, amorphous OSHA ACGIH NIOSH Supplier OHSA, CAN Mexico Brazil Silica, amorphous OSHA ACGIH NIOSH Supplier OHSA, CAN Mexico Brazil Barium sulfate OSHA ACGIH NIOSH Supplier OHSA, CAN Mexico Brazil Brazil OSHA ACGIH NIOSH Supplier OHSA, CAN Mexico Brazil OHSA, CAN Mexico Brazil

Exposure

		Brazil	No Established Limit
	Bis (1,2,2,6,6-pentamethyl-4-piperidinyl)	OSHA	No Established Limit
	sebacate	ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0082919-37-7		OSHA	No Established Limit
	PENTAMETHYL-4-P	ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
TS-KH8070	SECONDARY DIAMINES	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit

Health Data

CAS No.	Ingredient	Source	Value
0000110-43-0	Methyl n-amyl ketone	NIOSH	Irritation; liver kidney
0000763-69-9	Ethyl 3-ethoxypropionate	NIOSH	No Established Limit
0001344-28-1	Aluminum oxide	NIOSH	No Established Limit
0007631-86-9	Silica, amorphous	NIOSH	No Established Limit
0007727-43-7	Barium sulfate	NIOSH	Eye nose
0012136-45-7	Potassium oxide	NIOSH	No Established Limit
0014807-96-6	Talc	NIOSH	(containing asbestos); Fibrotic pneumoconiosis; (containing no asbestos); Nonmalignant respiratory effects
0041556-26-7	Bis (1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	NIOSH	No Established Limit
	DECANEDIOIC ACID, METHYL 1,2,2,6,6- PENTAMETHYL-4-P	NIOSH	No Established Limit
TS-KH8070	SECONDARY DIAMINES	NIOSH	No Established Limit

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000110-43-0	Methyl n-amyl ketone	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000763-69-9	Ethyl 3-ethoxypropionate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0001344-28-1 Aluminum oxide		OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0007631-86-9	Silica, amorphous	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;

0007727-43-7	Barium sulfate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0012136-45-7	Potassium oxide	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0014807-96-6	Talc	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0041556-26-7	Bis (1,2,2,6,6-pentamethyl-4- piperidinyl) sebacate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0082919-37-7	DECANEDIOIC ACID, METHYL 1,2,2,6,6-PENTAMETHYL-4-P	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
TS-KH8070	SECONDARY DIAMINES	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

8.2. Exposure controls

Respiratory	Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.
Eyes	Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Skin	Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Engineering Controls	Depending on the site-specific conditions of use, provide adequate ventilation.
Other Work Practices	Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.

9. Physical and chemical properties

•

Coloured Liquid Not Measured No Established Limit Not Measured 35 (C) 95 (F) 39 (C) 102 (F)

Evaporation rate (Ether = 1)	Not Measured
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: 1
	Upper Explosive Limit: No Established Limit
vapor pressure (Pa)	Not Measured
Vapor Density	Heavier than air
Specific Gravity	1.29
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	No Established Limit Not Measured
VOC %	Refer to the Technical Data Sheet or label where information is available.

9.2. Other information

No further information

10. Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

FLAMMABLE/COMBUSTIBLE MATERIALS: Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks) creating a vapor explosion hazard. Runoff to sewers may create fire or explosion hazard. Containers may explode when heated.

11. Toxicological information

Acute toxicity

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr
SECONDARY DIAMINES - (TS-KH8070)	No data available	No data available	No data available	No data available
Barium sulfate - (7727-43-7)	3,000.00, Mouse - Category: 5	No data available	No data available	No data available

Methyl n-amyl ketone - (110-43-0)	1,670.00, Rat - Category: 4	12,600.00, Rabbit - Category: NA	No data available	No data available
Talc - (14807-96-6)	No data available	No data available	No data available	No data available
Ethyl 3-ethoxypropionate - (763-69-9)	4,300.00, Rat - Category: 5	9,500.00, Rabbit - Category: NA	No data available	No data available
Silica, amorphous - (7631-86-9)	5,110.00, Rat - Category: NA	5,000.00, Rabbit - Category: 5	No data available	No data available
Aluminum oxide - (1344-28-1)	5,000.00, Rat - Category: 5	No data available	No data available	No data available
Potassium oxide - (12136-45-7)	No data available	No data available	No data available	No data available
Bis (1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate - (41556-26-7)	2,615.00, Rat - Category: 5	No data available	No data available	No data available
DECANEDIOIC ACID, METHYL 1,2,2,6,6-PENTAMETHYL-4-P - (82919-37-7)	No data available	No data available	No data available	No data available

Item	Category	Hazard
Acute Toxicity (mouth)	Not Classified	Not Applicable
Acute Toxicity (skin)	Not Classified	Not Applicable
Acute Toxicity (inhalation)	Not Classified	Not Applicable
Skin corrosion/irritation	Not Classified	Not Applicable
Eye damage/irritation	Not Classified	Not Applicable
Sensitization (respiratory)	Not Classified	Not Applicable
Sensitization (skin)	1	May cause an allergic skin reaction.
Germ toxicity	Not Classified	Not Applicable
Carcinogenicity	Not Classified	Not Applicable
Reproductive Toxicity	Not Classified	Not Applicable
Specific target organ systemic toxicity (single exposure)	Not Classified	Not Applicable
Specific target organ systemic Toxicity (repeated exposure)	Not Classified	Not Applicable
Aspiration hazard	Not Classified	Not Applicable

12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
SECONDARY DIAMINES - (TS-KH8070)	Not Available	Not Available	Not Available
Barium sulfate - (7727-43-7)	59,000.00, Poecilia sphenops	32.00, Daphnia magna	Not Available
Methyl n-amyl ketone - (110-43-0)	131.00, Pimephales promelas	Not Available	Not Available
Talc - (14807-96-6)	Not Available	Not Available	Not Available
Ethyl 3-ethoxypropionate - (763-69-9)	50.00, Pimephales promelas	480.00, Daphnia magna	115.00 (72 hr), Selenastrum capricornutum

Silica, amorphous - (7631-86-9)	10,000.00, Danio rerio	10,000.00, Daphnia magna	10,000.00 (72 hr), Scenedesmus subspicatus
Aluminum oxide - (1344-28-1)	Not Available	Not Available	Not Available
Potassium oxide - (12136-45-7)	Not Available	Not Available	Not Available
Bis (1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate - (41556-26-7)	1.00, Lepomis macrochirus	20.00, Daphnia magna	Not Available
DECANEDIOIC ACID, METHYL 1,2,2,6,6- PENTAMETHYL-4-P - (82919-37-7)	Not Available	Not Available	Not Available

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available

13. Disposal considerations

13.1. Waste treatment methods

Do not allow spills to enter drains or watercourses.

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. Transport information

14.1. UN number 14.2. UN proper shipping nar 14.3. Transport hazard class(
DOT (Domestic Surface	Transportation)	IMO / IMDG (Ocea	n Transportation)
DOT Proper Shipping Name	PAINT	IMDG Proper Shipping Name	PAINT
DOT Hazard Class	3	IMDG Hazard Class Sub Class	3 3
UN / NA Number	UN 1263		
DOT Packing Group	н	IMDG Packing Group	П
CERCLA/DOT RQ	3867 gal. / 41667 lbs.	System Reference Code	28
14.4. Packing group	П		
14.5. Environmental hazards			
IMDG Marine Pollut	ant: No		

14.6. Special precautions for user Not Applicable 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not Applicable

15. Regulatory information

Regulatory Overview	The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.
WHMIS Classification	B3 D2B
DOT Marine Pollutants (1 (No Product Ingred	
DOT Severe Marine Pollu (No Product Ingred	
EPCRA 311/312 Chemica	als and RQs (>.1%) :
BUTYL ACETATE acetate))	(5000 lb final RQ (listed under Butyl acetate); 2270 kg final RQ (listed under Butyl
Xylenes (o-, m-, p	- isomers) (100 lb final RQ; 45.4 kg final RQ)
EPCRA 302 Extremely Ha (No Product Ingred	
EPCRA 313 Toxic Chemi	cals (>.1%) :
Aluminum oxide	
Xylenes (o-, m-, p	- isomers)
Mass RTK Substances (>	1%) :
Aluminum oxide	
Barium sulfate	
Methyl n-amyl ket	one
Silica, amorphous	
Talc	
Penn RTK Substances (>	1%) :
Aluminum oxide	
Barium sulfate	
Methyl n-amyl ket	one
Silica, amorphous	
Talc	
Penn Special Hazardous (No Product Ingred	
RCRA Status: (No Product Ingred	ients Listed)
N.J. RTK Substances (>1	%):
Aluminum oxide	
Barium sulfate	
Methyl n-amyl ket	one
Potassium oxide	
Silica, amorphous	
Talc	

N.J. Special Hazardous Substances (>.01%) :

Calcium oxide

Benzene, ethyl-

BUTYL ACETATE

Potassium oxide

Talc

Xylenes (o-, m-, p- isomers)

N.J. Env. Hazardous Substances (>.1%) :

Aluminum oxide

Xylenes (o-, m-, p- isomers)

Proposition 65 - Carcinogens (>0%):

Benzene, ethyl-

Formaldehyde

Proposition 65 - Female Repro Toxins (>0%): (No Product Ingredients Listed)

Proposition 65 - Male Repro Toxins (>0%): (No Product Ingredients Listed)

Proposition 65 - Developmental Toxins (>0%): (No Product Ingredients Listed)

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapor.

H226 Flammable liquid and vapor.

H302 Harmful if swallowed.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

This is the first revision of this SDS format, changes from previous revision not applicable.

End of Document